

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1-60. (Cancelled)

61. (Currently Amended) A refrigeration system comprising:

a plurality of refrigeration circuits each having an evaporator pressure regulator, an expansion valve, and an evaporator in fluid communication, wherein said evaporator pressure regulator regulates suction pressure for a respective refrigeration circuit and said expansion valve ~~expands~~ controls refrigerant superheat through a respective evaporator;

at least one compressor in fluid communication with said plurality of refrigeration circuits and operable to output a cooling capacity;

a sensor operable to indicate a cooling demand for said plurality of refrigeration circuits; and

a control system operable to control said evaporator pressure regulators independently of said expansion valves for each of said plurality of refrigeration circuits, wherein said control system adaptively controls said cooling capacity to meet said cooling demand and operates one or more of said evaporator pressure regulators at approximately fully open.

Best Available Copy

62. (Previously Presented) The system of Claim 61, wherein said cooling demand is determined by monitoring at least one of the following: refrigeration circuit pressure, refrigeration case temperature, product temperature, and valve opening percent.

63. (Previously Presented) The system of Claim 61, wherein said control system adaptively controls said suction pressure of each of said plurality of refrigeration circuits through control of a valve position of each of said plurality of evaporator pressure regulators.

64. (Previously Presented) The system of Claim 63, wherein said control system adaptively controls said suction pressure of each of said plurality of refrigeration circuits through control of a valve position of each of said plurality of evaporator pressure regulators and at least one of refrigeration circuit pressure, refrigeration case temperature, and product temperature.

65. (Currently Amended) A refrigeration system comprising:

a plurality of refrigeration circuits each having an evaporator pressure regulator, an expansion valve, and an evaporator in fluid communication, said evaporator pressure regulator regulating suction pressure for a respective refrigeration circuit and said expansion valve ~~expanding~~ controlling refrigerant superheat for a respective evaporator;

at least one compressor in fluid communication with said plurality of refrigeration circuits and operable to output a cooling capacity;

a sensor assembly operable to measure operating parameters of said plurality of refrigeration circuits; and

a control system operable to determine a cooling demand based on said operating parameters, control said at least one compressor to output said cooling capacity to meet said cooling demand, and control suction pressure of each refrigeration circuit by controlling a position of said evaporator pressure regulator independently of said respective expansion valve in each of said plurality of refrigeration circuits.

66. (Previously Presented) The system of Claim 65, wherein said control system is further operable to position at least one of said evaporator pressure regulators approximately fully open while controlling said cooling capacity to meet said cooling demand.

67. (Previously Presented) The system of Claim 65, wherein said controller is operable to control said suction pressure until said evaporator pressure regulator is one hundred percent open.

68. (Previously Presented) The system of Claim 65, wherein said controller adaptively controls said suction pressure for each of said plurality of refrigeration circuits

based on said operating parameters and said position of said evaporator pressure regulator.

69-73. (Cancelled)

74. (Currently Amended) A method comprising:

determining a cooling demand for a plurality of refrigeration circuits;

operating an electronic evaporator pressure regulator for each of said plurality of refrigeration circuits to regulate a suction pressure of a respective refrigeration circuit;

operating an expansion valve to ~~superheat control~~ refrigerant superheat in each of said respective refrigeration circuits;

measuring an operating parameter for at least one of said refrigeration circuits;

and

controlling each of said electronic evaporator pressure regulators independently of said expansion valves for said respective refrigeration circuit; and

meeting said cooling demand while adaptively controlling at least one of said evaporator pressure regulators to an approximately fully open position based upon said measuring.

75. (Previously Presented) The method of Claim 74, wherein said measuring includes measuring a refrigerant pressure.

76. (Previously Presented) The method of Claim 75, wherein said controlling includes controlling said evaporator pressure regulators based upon said refrigerant pressure measurement.

77. (Previously Presented) The method of Claim 74, wherein said measuring includes measuring temperature.

78. (Previously Presented) The method of Claim 77, wherein said controlling said electronic pressure regulators includes averaging said temperature measurement.

79. (Previously Presented) The method of Claim 77, further comprising determining an error value between said temperature measurement and a circuit temperature set point.

80. (Previously Presented) The method of Claim 79, further comprising determining a percent value opening for said evaporator pressure regulators based upon said error value and electronically adjusting a valve position of said evaporator pressure regulators.

81. (Previously Presented) The method of Claim 80, further comprising determining said cooling demand based on one or both of said error value and said valve position.

82-88. (Cancelled)

89. (Currently Amended) A refrigeration system comprising:

a plurality of refrigeration circuits each having an evaporator pressure regulator, an expansion valve, and an evaporator in fluid communication, wherein said evaporator pressure regulator regulates suction pressure for a respective refrigeration circuit and said expansion valve ~~expands~~ controls refrigerant superheat through a respective evaporator;

at least one compressor in fluid communication with said plurality of refrigeration circuits and operable at a compressor capacity between a minimum and maximum compressor capacity;

a temperature sensor operable to measure a refrigeration case temperature of at least one of said plurality of refrigeration circuits; and

a control system operable to control said evaporator pressure regulators independently of said expansion valves for each of said plurality of refrigeration circuits, wherein said control system determines said compressor capacity based on a valve position of said at least one evaporator pressure regulator and said refrigeration case temperature.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.